



METROLOGY LAB PRECISION ON THE PRODUCTION LINE

ISO 17025 accredited









25+ YEARS OF METROLOGY EXPERIENCE



THE INLINE SOLUTION

Rely on a robust tool

Proven to take 1 million measurements in one year.

Take ultra-fast measurements

The GapGun PRO2 has a measurement cycle of just 1 second.

Enjoy a portable and ergonomic tool

The GapGun PRO2 can be taken to the part and can run for up to 8 hours. 100% operator approved.

THE TOOL FOR OFFLINE QUALITY CONTROL INSPECTION

Measure 100s of points of the car easily

The full colour graphic check plans can be tailored to your application and show operators exactly where to measure.

Ensure an audit trail for all measurements

GapGun PRO2 captures measurement digitally. Sensors are calibrated in an ISO17025 certified laboratory.

Get repeatable results

For the sharpest business intelligence.



"Our new handheld laser scanners from Third Dimension ensure perfect consistency in all body surfaces to a tolerance of just 0.025 mm for panel gaps, and 0.01 mm for flush measurements – imperceptible to the human eye. One colleague can do 140 checks in 6 minutes! Due to global demand for our products we must also ensure efficiency, so our colleagues' skills are increasingly augmented by innovation and cutting edge technology."

Automotive OEM UK













Fast

Accurate

Repeatable

Non-contact

Tracable

THE GAPGUN PRO2 COMES EQUIPPED WITH A MARKET LEADING RANGE OF FEATURES





CREATE BESPOKE CHECKPLANS

SPC3d Software lets you define sequences of measurements including photos that users can follow with minimal training.



SHARE MEASUREMENT PLANNING

Manage multiple GapGun PRO2s using one software, SPC3d, and have multiple operators working at once from one plan.



TOUCH SCREEN INTERFACE

Navigate through checkplans easily with GapGun PRO2's touch screen.



EXPORT MEASUREMENT RESULTS EASILY

Export measurement results easily to CSV, SQL, XML, Excel, PDF and other file formats. Interface with most leading SPC packages such as QDAS.



ON SCREEN RESULTS ANALYSIS

View cross sections of the measurement area and results analysis on-screen using standard red/green colouring conventions and warning sounds to indicate go/no go conditions.



CHANGEABLE SENSOR HEADS

Our trademarked "VChange" mechanism mean you can switch between sensor heads easily and guickly.



ACCESS HARD-TO-REACH PLACES WITH EXTENSION CABLE

Take measurements in awkward and small places, when you use the sensor head extension cable.



FULLY INTEGRATED WI-FI CAPABILITY

Feed measurement back to your production systems in real-time.



MULTIPURPOSE DESK DOCK CABLE

Download data straight to the PC and charge simultaneously.



HI-RANGE SENSOR HEAD CAPABILITY

Measure a range of surfaces including head lights, chrome, high gloss black paint and carbon fibre.

ONE TOOL INFINITE APPLICATIONS




GAP AND FLUSH INTERIORS





GAP AND FLUSH EXTERIORS



GAP AND FLUSH LIGHTS











RADII







CHAMFERS






WELD AND SEALS





ANGLES



T-SERIES SENSOR HEAD SPECIFICATION





Sensor head T60-V

Sensor head T15-M

| Laser | Laser Class 2M with automatic laser intensity adjustment | | | | |
|---------------------------------|--|---------------|---|---------------|--|
| Operating temperature | 0 to 40°C (32 to 104°F) | | | | |
| Shock protection | Shock protection jacket on sensor, and high impact plastic housing | | | | |
| Software | GapGun version 8.1 software | | | | |
| Operating temperature | 0 to 40°C (32 to 104°F) | | | | |
| Storage temperature | -20°C to 60°C (-4 to 140°F) | | | | |
| Traceability and calibration | Calibrated under ISO 17025*** | | | | |
| Example Measurement capability* | T60 | | T15 | | |
| Gap = 0.3 mm | Max bias 0.06 | Max SD**0.025 | Max bias 0.03 | Max SD**0.015 | |
| Flush = 1 mm | Max bias 0.04 | Max SD**0.01 | Max bias 0.03 | Max SD**0.01 | |
| Radius 0.25 to 1.0mm | | | Max bias 0.013 | Max SD**0.005 | |
| Edge radius 0.25 to 1.9mm | | | Max bias 0.015 | Max SD**0.02 | |
| Chamfer 0.25 to 1.9mm | | | Max bias 0.015 | Max SD**0.012 | |
| Field of view | 60 mm | | 15 | mm | |
| Size | 41 x 56 x 99 (1.6x2.2x3.9") WxDxH, Inc jacket | | 36x60x83mm (1.2x1.9x2.7") WxDxH, Inc jacket | | |
| Weight | 170g (5.9 oz) | | 175g (6.1 oz) | | |

^{*}according to D19-034 Third Dimension specification under request

ACCESSORIES AND OPTIONS

Included

| Docking Station | Charge the GapGun PRO2 and upload data directly to a PC. | |
|------------------------|--|--|
| Battery Pack | Use for longer with the light-weight battery pack. | |
| Belt Clip | Carry the GapGun PRO2 with ease. | |
| Calibration Block | Calibrate with ease. | |
| Standard Stand-off set | Enables fast and reproducible measurements. | |
| Optional | | |
| Head Extension Cable | Take measurements in tight and hard to access locations. | |

Customised Stand-off setCustom standoffs available on request.Specific CalibrationWe offer specific calibration services under request.

YOUR LOCAL DISTRIBUTOR WILL BE HAPPY TO HELP ADVISE YOU ON THE BEST SENSOR HEAD AND ACCESSORIES FOR YOUR APPLICATION. TO FIND A DISTRIBUTOR NEAR YOU SIMPLY EMAIL SALES@THIRD.COM

^{**}Standard deviation

^{***}Gap and Flush

GAPGUN PRO2 DATA COLLECTOR





| Display | Full colour, daylight readable LCD touchscreen | |
|-------------------------|---|--|
| Size | 97mm (3.8") | |
| Resolution | 640 x 480 pixel | |
| Ethernet | 100MBPS fast ethernet | |
| Feedback | Audio output and haptic feedback | |
| Operating temperature | 0 to 40C (32 to 104F). Internal battery charging limited at higher temperatures | |
| Peripheral devices | USB 2.0 port | |
| Power rating (battery) | 4W (4.2v @ 0.95A) | |
| Power rating (charging) | 6W (12v @ 0.5A) | |
| Shock protection | Shock protecting cover on sensor and handle, and high impact plastic housing | |
| Size | 90 x 135 x 190mm (3.5 x 5.3 x 7.5") W x D x H) | |
| Software | GapGun version 8 software | |
| Storage temperature | -20°C to 60°C (-4 to 140°F) | |
| User interface | Click and drag touchscreen, trigger and power/reset button | |
| Weight | 460g (16oz) | |

IEEE 802.11 b,g,n

COMPATIBLE PC SOFTWARE

| | SPC3d software pack |
|---------|----------------------------------|
| ♣ SPC3d | For checkplan configuring virtua |

For checkplan configuring virtual measurement tools, data logging, reviewing measurements.

LINK

Link software pack

Allows custom .NET programs to be written controlling the GapGun PRO2 or Vectro devices.

Inspect software pack

For manual and interactive analysis of measurement data.



Inline software pack

Allows a large overhead display of measured results.

WARRANTY AND SERVICE

→ INSPECT

1-Year warranty as standard on GapGun PRO2 and all sensor heads.

Maintenance contracts available for hardware and software, bespoke software and hardware development.

Please contact your local Distributor or sales@third.com for more information.

Wireless



ABOUT

UK based company, Third Dimension design and manufacture the non-contact precision measurement systems, GapGun® (hand-held) and Vectro® (robotic). Established in 1995, Third Dimension has a long track record of supplying non-contact optical measurement equipment and services to the largest names in aerospace, automotive and energy sectors worldwide.

Holder of two Queen's Awards for Enterprise, our systems have been fully integrated into quality control processes by leading OEMs, Tier 1s and 2s in the automotive, aerospace and energy sectors, worldwide.

Achieving ISO 17025 status in 2019, Third Dimension continue to lead the way in non-contact precision measurement tooling.



"GapGun is the ideal tool for quickly and accurately measuring small gaps and profiles throughout the plane panels... it has saved time and money throughout the production process."

Aerospace OEM Germany

ARRANGE A DEMONSTRATION TODAY

Contact one of our expert Distributors in your area to arrange a free demonstration in your factory.

Unsure of who your local Distributor is?

Simply call +44(0)3333 44 3000 or email sales@third.com and we will talk through your requirements and put you in contact with the nearest Distributor to you.

GET IN CONTACT

- +44(0)3333 443 000
- sales@third.com
- www.third.com

FOLLOW US

- **@thegapgun**
- **ThirdDim**
- **Third-dimension**

Authorised Distributor

CUSTOMERS

Third Dimension's distribution network serves customers in 30+ countries worldwide. These include:







































GapGun and Vectro systems are designed, developed and manufactured by:



Third Dimension, 2 Brabazon Office Park, Golf Course Lane, Filton, Bristol, BS34 7PZ, United Kingdom. Tel: +44(0)3333 44 3000 Email: info@third.com ©2022 Third Dimension Software Ltd. All Rights Reserved.